AG-CRETE INDUSTRIES

AG-CRETE

Cattle Feedlot Products Precast to Last!

FEED TROUGHS

Economical: Prevent feed waste. Usually paid off within a year of purchase!

Durable: Precast concrete is long-lasting and will remain a saleable asset.

Portable: Cast-in lifting pins enable ease of unloading & positioning.

Easy to clean: Vertical sides and rounded inner corners

Optional: Galvanised end doors (sliding or hinged) can be added if required.



Deliveries throughout VIC, NSW, SA

Phone (03) 5450 4400 Email sales@ag-crete.com.au Visit www.ag-crete.com.au

SMALL BARRIERS / DIVIDER WALLS

Economical: Keep feed within reach in feed-pad laneways = save time & waste.

Durable: Precast walls are long-lasting and will remain a saleable asset.

Customise: Can be made to any height <900mm.

Portable: Cast-in lifting pins enable ease of unloading & positioning.

Secure: Glue or pin in place on existing slabs or cast into new slabs.





Style DW0500 DW0900 Height x Width x Length 500 x 300 x 3000mm 900 x 300 x 6000mm

Weight 680kg 1760kg

Weight 1220kg 2250kg

FEEDLOT WATER TROUGHS

Many other trough types		AG-CRETE INDUSTRIES (03) 5450 4400	
	AG-CRE INDUSTRIE (03) 5450 44	Float cove	r pivots on s steel bar
available! Please ask	Style LT3000F LT4800F	Length x Width x Height 3000 x 700 x 700mm 4800 x 735 x 700mm	t Capacit 485Lt 980Lt
AG-CRET T (03) 5450 44		FRIES Dagcrete.com.av	Available Fr

2 Mibus St, Kerang Vic 3579

F (03) 5450 3119

Extra high at 700mm: Ideal for cattle! **Pipework** can be enclosed within base. 240-300mm clear height underneath.

2 side openings with stainless covers for access to plumbing. (350 x 170mm)

Brass inlet socket: 32mm (11/4") BSP in base, under hinged float cover.

Brass outlet socket: 75mm (3") BSP in base with plug or a riser pipe for trough overflow (optional).

Optional paint inside = easier to clean. **Optional float valves** & other fittings.

om: